



XNC-422BP

4U Industrial PC Chassis



Technical Informations

FEATURES

- Excellent Thermal Solution:
 - Optional fans on rear window
 - Easy-swap front fan w/removable fan filter
- Great Flexibility & Expandability
 - Two-way usage for rackmount & stand -alone
 - Optional 22" mounting rail
 - Optional top cover and foot stand for stand-alone
 - 2 x Front USB 2.0 ports
- System Security Design
 - Chassis intrusion switch
 - Metal front door w/key lock
 - Reset switch to disable audible warning
 - Rotate-able device cage for rackmount & stand-alone
- Dust -Free
 - Removable fan filter
- Anti-Vibration
 - Up to 2pcs of card-retainer to avoid the vibration of add-on cards
 - Device brackets with rubber for anti-vibration
 - Optional mounting plate
 - Changeable optional slot bracket
- Optional 7 slot bracket with SCSI ports
- Optional 15 slot bracket for backplane

SPECIFICATONS

- M/B form factor
 - ATX (12"x9.6") or Extended ATX (12"x10.5")
- CPU Type
 - UP Intel P4/DP Intel Nocona/DP AMD Opteron
- Dimension (DxWxH)
 - mm:522"x 430"x 177"
 - inch:20.5" x 16.9" x 7"
- Drive Bays
 - External:
 - 5.25": 3
 - 3.5": 2
 - Internal:
 - 3.5": 3
 - HDD Trays:N/A
- Standard
 - EIA-RS310D
- PSU
 - Form Factor:PS/2 Single /Mini-Redunant
 - Watts:up to 550 W
- Front Controls
 - Power ON/OFF,System Reset
- Indicators
 - Power ON/OFF,HDD/LAN Activity
- Slot Openings
 - 7 or 15
- Cooling Fan
 - Standard:1 x 120 mm front fan
 - Optional:2 x 80 mm rear fan (easy swap)
- Riser Card
 - N/A
- Material
 - SECC
- Sheet Metal Tickness
 - 1.2mm



CORTEX
INDUSTRIAL SYSTEMS



Net Weight
11.5kg
Sheet Metal Thickness
1.2mm
Backplane
N/A
Front Bezel Option
N/A
Cubic Feet
3.56
System Security
Intrusion Switch

APPLICATIONS

Graphics Workstations
Corporate Files Servers
Video-on-Demand
Security and Surveillance Systems



Rua Funchal, 513, 12o andar
Vila Olímpia - São Paulo - CEP 04551-060 - (11) 3351-4486
www.cortex.com.br